Image	Part Number
	Trelawny : 320.002H
	IMPA: 59.22.49 ISSA: 55.096.16 Trelawny: 320.0020
	IMPA: 59.22.49 ISSA: 55.096.18 Trelawny:
	320.5500
	IMPA: 59.22.41 ISSA: 55.096.10
0	Trelawny:

	020.7000
	Trelawny : 320.3658
	IMPA: 59.22.42 ISSA: 55.096.11
	Trelawny : 320.5120
	IMPA: 59.22.43 ISSA: 55.096.12
	Trelawny : 320.4140
-11111	Trelawny : 320.9622
	Trelawny : 320.9612

* W W W W W	1 1
	Trelawny : 320.1020ST
	Trelawny : 320.1020SS
	Trelawny : 320.1020SB
	Trelawny : 320.9620
	IMPA: 59.22.45 ISSA: 55.096.13
	Trelawny:
	320.9610

IMPA: 59.22.44 ISSA: 55.096.14

	Further
Description	Information
Heavy Duty Drum Complete with 12mm shafts	Fitted as standard on all TFP200 machines
Cutter Shafts	
12mm Diameter	4 pieces required per drum
Tungsten Carbide Tipped Cutters 5 tips	80 pieces required per drum
Tungsten Carbide Tipped Cutters	80 pieces required per

	drum
6 tips	
Star Cutters	208 pieces required per drum
Beam Cutters	264 pieces required per drum
Spacers	88 pieces required per
Used to create a gap in between TCT cutters	drum - TCT
Twisted Knot Wire Brush Refill	21 pieces required per
Crimped Wire Brush Refill	drum 14 Pieces required per drum
Drum Assembly	

TCT Cutters	Consists of drum, 4 12mm shafts, 80 TCT cutters & 88 spacers
Drum Assembly	
Star Cutters	Consists of drum, 4 12mm shafts, 80 TCT cutters & 88 spacers
Drum Assembly	
Beam Cutters	Consists of drum, 4 12mm shafts & 208 star cutters
Drum Assembly	
Twisted Knot Wire Brush	Consists of drum & 21 twisted wire brush segments
Drum Assembly	
Crimped Wire Brush	
	Consists of drum & 14

I	crimpea wire
	brush segments